DT119

DELTATEK 5000 DISPOSABLE OVERALLS WITH HOOD - 4B TYPE - TAPED SEAMS

Model DT119



Product specifications

Overall with elasticated hood. 4-B type. Non-woven microporous laminate Deltatek 5000. Fastening with zip under adhesive flap (top and bottom opening). Elasticated waist and ankles. Knitted wrist. Antistatic. Single-use. Individual airtight pack.

Front: Microporous laminate 60 g/m².
Back: SMS 52 g/m².

COLOR
White

SIZE
MD, LG, XL, 2X

Product Features and Benefits

	DELTATEK 5000	Polyethylene film ensures better a resistance to chemical attack and better mechanical resistance (abrasion - tearing).
	3-part hood	Supports head movement for increased comfort
	Closure with self-adhesive flap	Very good seal
	Ribbed cuffs	Good hold of the glove on the hand
	Elasticated ankles	
		
		
	Microporous laminate	No risk of lint Very soft
	Sealed seams Decontamination	Decontamination work
	DELTATEK 5000	

Certifications and Standards

CE

REGULATION (EU) 2016/425

EN ISO 13688:2013 General requirements for protective clothing.



EN14605:2005+A1:2009 Performance requirements for clothing with liquid-tight (Type 3) or spray-tight (Type 4) connections.

TYPE 4B: Protection against liquid chemicals (mists) - Type 4B



EN ISO 13982-1:2004+A1:2010 Protective clothing for use against solid particulates - Type 5 clothing

5B: Protection against dust (asbestos) + biological protection Type 5B



EN13034:2005+A1:2009 Performance requirements for chemical protective clothing offering limited protective performance against liquid chemicals (Type 6 equipment)

6B: Limited protection against liquid chemicals + biological protection Type6B



EN14126:2003+AC:2004 Protective clothing - Performance requirements and tests methods for protective clothing against infective agents



EN1149-5:2018 Electrostatic properties - Part 5: Material performance and design requirements

.: Surface resistivity inferior or equal to 2.5 x10^9 Ohms on one surface at least following EN1149-1



EN ISO 27065:2017 Performance requirements for protective clothing worn by operators applying pesticides and for re-entry workers

C1: Low exposure risk protection level against pesticides (C1).

Item details

Item details	Bar code	COLOR	SIZE		
DT119TM	3295249103200	White	MD	20	-
DT119GT	3295249103217	White	LG	20	-
DT119XG	3295249103224	White	XL	20	-
DT119XX	3295249103231	White	2X	20	-